

# MULTIPANEL TILE ADHESIVE RECOMMENDATIONS

The following products have been tested by the manufacturers and approved for use on MULTIPANEL.



ARDEX recommends that for direct tiling on external decks and internal wet areas the systems for MULTIPANEL are:

PRIMER		ADHESIVE		
WPM300 + Broadcast Sand	Abaflex	X77 +/- E90	X18 +/- E90	STS8W + E90 X56 (Covered external only)
Abapoxy + Broadcast Sand	Abaflex	X77 +/- E90	X18 +/- E90	STS8W + E90 X56 (Covered external only)



MAPEI recommends that for direct tiling on external decks and internal wet areas the systems for MULTIPANEL are:

PRIMER	PRODUCT	DETAIL
MAPEPRIM SP	Kerabond Plus mixed with Isolatic	(Two part normal set and cure tile adhesive)
	Granirapid	(Two part Rapid set and cure tile adhesive)
	Mapelastc Smart	(Cementitious waterproofing membrane) + Any Mapei Tile adhesive

\*\*\*Please note when using any MAPEI system MULTIPANEL must be pre-primed with Mapeprim SP (two component epoxy primer/bonding agent)



RLA recommends that for direct tiling on external decks and internal wet areas the systems for MULTIPANEL are:

PRIMER	ADHESIVE
RLA RL20G Moisture Barrier 2 part water based epoxy	Use RLA/ATLAS Just-2-Ezy 2Part Tile Adhesive to fix tiles as per the published instructions. Mix 6.5L of Uniflex Additive with 1 bag of Just-2-Ezy (15Kg). Tiles must be fixed in accordance with AS3958.1:2007. Particular attention should be given to adhesive coverage. Do Not Spot Fix Tiles.



ATA recommends that for direct tiling on external decks and internal wet areas the systems for MULTIPANEL are:

PRIMER	INTERNAL TILE INSTALLATIONS	EXTERNAL TILE INSTALLATIONS
Aus-Bond Ultra-Prime	Aus-Flex or Aus-Crete Adhesives	Aus-Crete Adhesives



SIKA recommends that for direct tiling on external decks and internal wet areas the systems for MULTIPANEL are:

PRIMER	ADHESIVE
Eco Systems Prep n Prime	Eco Systems Prep N Prime + Any sika tile adhesive



GRIPSET recommends that for direct tiling on external decks and internal wet areas the systems for MULTIPANEL are:

PRIMER	ADHESIVE
Gripset OP Beta Super Primer	Monoflex

- / It is the responsibility of the specifier to ensure the adhesives and their relevant systems comply with all relevant codes and regulations and system manufacturer recommendations.
- / All tiling should be carried out in accordance with Australian Standard AS3958.1:2007 – A Guide to Tiling.
- / Any waterproofing should be carried out in accordance with Australian Standard 4654.2:2012 – Exterior Waterproofing Installation.
- / All recommendations are subject to MULTIPANEL having been installed in accordance with the MULTIPANEL Balcony Substrate Waterproofing System document
- / Prior to commencing please review full specifications by contacting the manufacturer direct or call MULTIPANEL on (03) 9787 2544

**MULTIPANEL**



Waterproof Building Panels

MultiPanel Pty Ltd  
 Level One 110 Mt Eliza Way  
 Mt Eliza VIC Australia 3930  
 Phone +61 3 9787 2544  
 Fax +61 3 9787 9582  
 Email info@multipanel.com.au  
 www.multipanel.com.au

